

**DECLARATION OF PERFORMANCE NO 01CE/Bla/CSE/04**

1. The unique identification code of the product type: **01/Bla/UGL/CSE**
2. Intended use or use:  
**Dry-pressed ceramic tiles with low water absorption  $E_b \leq 0,5\%$ ; Annex G; Bla group, unglazed (UGL) Gres Porcellanato; for interior and exterior walls and floors of buildings - as described on the packaging.**
3. Manufacturer: **CERSANIT S.A.; AL. Solidarności 36; 25-323 Kielce**
4. System(s) of assessment and verification of constancy of performance: **SYSTEM 4**
5. Harmonised standard: **EN 14411:2012**
6. Declared performance:

<i>Essential characteristics</i>	<i>Performance (level and/or class)</i>	<i>Harmonised technical specification</i>
<b>Reaction-to-fire performance</b>	A1 <sub>FL</sub>	Classified Without Testing (CWT)
<b>Release of dangerous substances:</b>		
- Cadmium	Max 0,07mg/dm <sup>2</sup>	EN 14411:2012
- Lead	Max 0,8mg/dm <sup>2</sup>	
<b>Breaking strength:</b>		
- thickness $\geq 7,5mm$	$\geq 1300N$	
- thickness $< 7,5mm$	$\geq 700N$	
<b>Bond strength/adhesion [N/mm<sup>2</sup>]:</b>		
- cementitious adhesives	NPD - No Performance Determined	
- dispersion adhesives		
- reaction resin adhesives		
- mortar		
<b>Slippage according to CEN/TS 16165:2012, Annex B</b>	NPD – R13	
<b>Thermal shock resistance</b>	Meets	
<b>Durability for:</b>		
- internal use:	Meets	
- external use: resistance to freeze-thaw cycles	Meets	
<b>Tactility</b>	NPD - No Performance Determined	

A copy of the Declaration of Performance is available on the website: [www.cersanit.com](http://www.cersanit.com)

The performance of the above product is in accordance with the Declaration of Performance. This declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer referred to above.

Signed on behalf of the manufacturer:

QUALITY SYSTEM MANAGER  
  
 Jolanta Grzebna

Kielce, 01.06.2017  
(place and date of issue)

.....  
(signature)